

HOFS

SPDL86
TFT-LCO

Fiche produit

Les écrans interactifs HOFS s'adaptent facilement à tous types d'applications
Salle de conférence, salle de cour, grandes surfaces, musées...etc

Intéragissez à deux ou à plusieurs simultanément avec le doigt ou un stylet



Un écran tactile révolutionnaire

Technologie sans vidéo projecteur

Ecran tactile interactif FHD

Productivité dans les réunions

Rapidité dans la prise de decision

Specification	
Model No.	SPDL86
Panel size	86" TFT-LCO
Display area(mm)/mode	1428.48 x 803.52 mm (HxV)
Maximum resolution	1920x1080
Display color	16.7M
Pixel Pitch(mm)	0.63(H) x 0.63(V)
Brightness (nits)	450cd/m2
Contrast	1300:1
Visual angle	89/89/89/89 (Min.)(CR ≥ 10)
Response time	10(Typ.)(G to G) ms
Life(hrs)	>60,000(hrs)
Input and output	
HDMI	1
USB	2
Lan(Network version)	1
Speaker	2x5W(8Ω)
Video	
Color system	PAUNTSaSECAM
OSD display(screen menu display)	
menu language	Chinese/English
Power	
Power supply	AC100 ~ 240V 60/50 HZ
Maximum power consumption	≤ 220W
Standby power consumption	<5W
Temperature	
Working temperature	0°C~ 50°C
Storage temperature	20 °C ~60 °C
Working humidity	%85-%10
Storage humidity	%85-%10
Appearance	
Color/appearance	White,black,customized
Case	Metal case SPCC
Installation	Floor-standing
Certificate	CEFCC
Quality Standard	ISO9001 , CCC
Touch Panel(Optional)	
Specification	Infrared touch
Positioning accuracy	2±mms
Transmittance	≥ %92
Hardness	7H
Click manner	Multi points
Response time	≤ 10ms
Computer specifications	
Main chipset	Intel
CPU	I3
Graphics card	Integrated
Network card	Integrated 1/100/10 OOOM adaptive
Memory	4G DDRIII
Hard Disk	128G SSD
WIFI	Interated
Bluetooth	Integrated
Operation system	WN7/WIN8W1N10
Detailed functions	
Video format	MPEG1/MPEG1^2PEG4/DivX/ASP/WMV/AVI
Audio format	Wave/MP3AVMA/AAC
Image format	JPEG/BMP/TIFF/PNG/GIF
Image resolution	480P/720P/1080P



Rue Ali Layachi Rouiba Alger

Tél 023 85 50 80 Fax 023 85 52 73

contact@sadimet-dz.com

www.sadimet-dz.com