



46 inch 5.5mm narrow bezel lcd video wall display



LCD Panel

Resolution 1920×1080(H×V)
Pixel Pitch 0.53025×0.53025(mm)
Brightness 700(cd/ m)
Contrast Ratio 4000:1
Response Time 6ms
Display Color 16.7M
Viewing Angle 178°(H) / 178°(V)

Image

Aspect Ratio 16:09
Compensation Technology LTI,CTI
Motion Compensation Technology AUTO MOVE
Filter 3D combing filter, Digital noise reduction
Video Formats PAL,NTSC

Signal Source

Composite Video Input CVBS(BNC) ×1;
Composite Video Output CVBS(BNC) ×1 ;
Digital Signal Input HDMI×1; 1920x1080@60Hz Backwards compatible
Computer Signal Input VGA(DB-15) ×1; 1920x1080@60Hz Backwards compatible
Digital Signal Input DVI(DVI-I)×1; 1080P(1920×1080) Backwards compatible

Built-in Controller

Computer Centralized Control Interface RS232
Function Signals combine and display arbitrarily
Automatic Temperature Control Work automatically according to the set temperature and actual temperature of the machine to control fan operation

System

Image Signal Gain A more stable and correct image control
Operation Mode Computer centralized control
Bus Control I C
MTBF 50000 hs

Power Supply

Voltage 100~240V
Power Consumption 230W

Structure

Frame Size Upper side:3.5mm; lower side:1.7mm; left side:3.5mm; right:1.7mm
Installation Dimensions 1024mm×578.6mm×141.5mm
Display Area 1018.10mm×572.70mm
Installation Position 564×200(mm)
Material of Shell Metal
Installation Standard cabinets, custom cabinets

Rue Ali Layachi Rouiba Alger
Tél: 023 85 50 80/Fax: 023 85 52 73
contact@sadimet-dz.com
www.sadimet-dz.com